



C200CV

Coaxial Breakaway with Dual Check Valves



C200CV Coaxial Breakaway with Dual Check Valves

Avoid potentially disastrous situations with Catlow's C200CV Breakaway with dual check valves. The C200CV is designed to be used with Stage II vapor recovery coaxial hoses to interrupt the flow of fluid and vapors in the event of a break. The factory set 300 lb. pull-force helps minimize nuisance breaks and eliminates the risk of dispenser damage due to driveaways. Completely compatible with all major hose manufacturers, the C200CV offers minimal flow restriction, easy reconnection in the field and countless hours of safe, reliable service.

Features

- C.A.R.B. certified G-70-52-AM
- ETL Listed to UL Standard 567 Rev. 7
- Spring loaded poppets—stop the flow of fluid at both ends of the break
- Seals the flow of vapors to the dispenser
- Meets NFPA30A codes—federal and state regulations
- 300 lbs. maximum pull force
- Free repair kit with each breakaway
- Black foam cover provided
- One year warranty—factory repairable at no charge for one year from date of manufacture
- Reconnects on site in minutes using repair kit
- Field repairable—maintains ETL Listing
- Minimum flow restriction

Materials

- Body is cast aluminum
- O rings and seals are Viton

Accessories

- Repair kit ETL Listed (C200R)
- 10" whip hose (V010)
- Protective plastic cover (C200B-1)

CATLOW Inc. Sales Desk (800) 222-8569
Sales Fax (937) 898-8631 Phone (937) 898-3236
2750 US RT 40, Tipp City, OH 45371

©1999 CATLOW Inc. All Rights Reserved

C200CV95