

Thread Sealants **E-SEAL**



GE16



GE08



GE04

Gasoila E-SEAL Thread Sealant

- Non-hardening, non-toxic, opaque, dark green paste designed specifically for ethanol blended gasoline including E10 and E85.
- Use Gasoila 100 for 100% ethanol or 100% methanol applications.
- Provides a positive seal on pipe threads, joints, fittings, hoses, nozzles, pump assemblies, oil burners, hydraulics, bolts, compressors, engines, motors, fuel lines and couplings.
- For use on brass, copper, stainless steel, aluminum, black pipe, tin and galvanized pipe.
- Excellent resistance to gasoline, ethanol blended gasoline such as E10 and E85, petroleum solvents, kerosene diesel oil, biodiesel propane, butane, LPG, cutting oils, ammonia, aliphatic solvents, acids, steam and potable water.
- NOT for use with Oxygen.
- Temperature Range: -100°F to 800°F (-74°C to 318°C).
- Pressure Range: Up to 10,000 psi when sealing liquids and up to 3,000 psi with gases.
- UL Classified.
- For use on NPT Threads.

FPC Stock Code	Container Size	Units per Case
GE04	1/4 pt. Brush	24
GE08	1/2 pt. Brush	24
GE16	1 pt. Brush	12

