

Thread Sealants **SOFT-SET**

Gasoil® Soft-Set Thread Sealant with PTFE



SS16

- Soft-setting, non-toxic, PTFE paste.
- Provides a positive seal on pipe threads, joints, fittings, hoses, nozzles, LPG cylinders, pump assemblies, oil burners, hydraulics, compressors, engines, motors, housings, plugs, fuel lines, couplings, and more.
- Use on brass, copper, stainless steel, aluminum, black pipe, tin, galvanized, ABS, CPVC, PVC plastics, nylon, polyethylene, polypropylene, polybutylene and more.
- Excellent resistance to gasoline (up to 20% alcohol and petroleum blends), petroleum solvents, kerosene, diesel oil, propane, butane, LPG, cutting oils, ammonia, aliphatic solvents, acids, steam, potable water, compressed air and more.
- NOT for use on oxygen.
- Remains pliable in cold temperatures.
- Temperature Range: -100°F to 600°F (-74°C to 318°C).
- Pressure Range: To 10,000 psi sealing liquids; to 3,000 psi sealing gases.
- One year shelf life when stored at 40°F to 80°F (5°C to 27°C).
- For alcohol blended gasoline (ethanol) see E-seal on page 7.
- For use on NPT Threads.

FPC Stock Code	Container Size	Units per Case
SS01	1/8 oz. Tube	100
SS02	2 oz. Tube	36
SS04	1/4 pt. Brush	24
SS08	1/2 pt. Brush	24
SS16	1 pt. Brush	12
SB32	1 qt. Brush	6
SS28	1 Gallon	4
SS32	1 Qt. Flat Top	6
SSDC2	1/2 pt. Display Carton	1



Certified to
ANSI/NSF61

Certified to
ANSI/NSF14