

# HUSKY SAFE-T-BREAK® VALVES

## VACUUM ASSIST VAPOR RECOVERY

All Husky Safe-T-Breaks® stop the flow of fuel on both sides of the separation and have passed the demanding UL test requirements on separations without leaking or failing.

### Model 4034

- Reconnectable Safe-T-Break® for the vapor assist systems: coaxial hoses with fuel "outside" hose, vapor return "inside" hose.
- Meets the reconnect endurance test of the UL Standard 567 Ninth Edition.
- Unique vapor valve stops vapors from escaping after a drive away.
- Separates at less than 200 lbf / 889.6 N to minimize backlash damage.
- Unique pre-loaded shock absorbing wave spring minimizes nuisance breaks.

### Model 6560 (not shown)

- Reconnectable Safe-T-Break® designed for the Veeder-Root® 900301 and VST Enviro-Loc™ primary hose with ORVR valve.
- Same style and design as the Model 4034 including the same fuel/vapor paths and separation force.

### Model 6210 & 5134A

- Non-reconnectable Safe-T-Break® in the same style and design as the Model 4034 including the same fuel / vapor paths and separation force.



Model 4034



Model 6210

## SPECIFYING INFORMATION

Model Number	Description	Weight lbs.(kg.)
4034	Reconnectable Safe-T-Break®	.93 (.42)
4034A	Reconnectable Safe-T-Break® - Atex	.93 (.42)
6560	Reconnectable Safe-T-Break® for ORVR	.93 (.42)
6210	Non-reconnectable Safe-T-Break®	.93 (.42)
5134A	Non-reconnectable Safe-T-Break® - Atex	.93 (.42)

## CONSTRUCTION

Body	Aluminum
Seals	Fluorocarbon
Springs	Stainless Steel
Threads	4034, 4034A, 5134A & 6210 = M34 x 1.5 6560 = 1¼" - 18

Stainless steel load and latch spring reverse mechanism.

Hardened stainless steel latch ring and balls.



## PATENTS and LISTINGS

Patent Numbers: 4034 & 5134A = 4,827,977  
6560 & 6210 = pending

Listings:	4034	UL	California Environmental Protection Agency AIR RESOURCES BOARD
	6560	UL	Texas Commission on Environmental Quality
	6210	UL	
	4034A & 5134A	Ex	



MADE IN THE U.S.A.



# HUSKY SAFE-T-BREAK® VALVES

## VACUUM ASSIST VAPOR RECOVERY

- **Dimensions**
- **Accessories**

### Guards

Model No.	Description
3098	Scuff Guard for 4034, 4034A, 5134A, 6210 & 6560 Safe-T-Breaks®

### Testing and Maintenance

Model No.	Description
7000	Safe-T-Break® Drain Cup
5164	O-ring replacement kit for 5134A Safe-T-Break®

Model 4034 & 6560



Model 5134A & 6210

