

HARD-SET Thread Sealants

Gasoil® Hard-Set Thread Sealant

- Hard-setting, fast-drying, red varnish sealant.
- Use on brass, copper, stainless steel, aluminum, black pipe, tin, galvanized pipe, cadmium-plated metal, rubber, porcelain, wood, marble, epoxy, cork, corpreme, asbestos, plexiglass, some plastics, paper, felt and more.
- Excellent resistance to all aliphatic, aromatic, chlorinated solvents; naphthas, benzenes, all petroleum products, refrigerants, freons, propane, butane, kerosene, jet fuel, water, steam and more.
- NOT for use on alcohol content over 20%.
- NOT for use on oxygen.
- Temperature Range: -60°F to 350°F (-52°C to 178°C) (up to 550°F (290°C) intermittently).
- Pressure Range: To 500 psi sealing face or butt joints; to 15,000 psi for threaded connections.
- Dries to touch within 30 minutes; thorough drying may take 24 to 48 hours.
- One year shelf life when stored at 40°F to 80°F (5°C to 27°C). Flammable.



FPC Stock Code	Container Size	Units per Case
BT04	1/4 pt. Brush	24
BT08	1/2 pt. Brush	24
BT16	1 pt. Brush	12
FT32	1 qt. Flat Top	6
FT28	1 Gallon	4

