OPW 634 Series Tight-Fill Top-Seal Caps

Tight-Fill Top-Seal Caps are installed on top-seal adaptors, when not in use, to prevent gasoline vapors from escaping and to prevent water, dust and debris from entering the tank.

Look for this label for authentic OPW EVR Approved products.
EVR Approved for E85

Materials

Cap & Links: Duratuff®
Pins: Stainless steel
Gasket: Nitrile
Color: Grey



Ordering Specifications

Product #	in.	mm	lbs.	kg
634TT-7085-EVR	4	102	1.01	.46

Replacement Parts

Part #	Description
H15005M	Nitrile Gasket



634TT

NOTE: Effective height above adaptor: 1-19/32"

OPW 634TT

The OPW 634TT is designed to mate with 4" 633T, 633TE, 61SA, 633TC, and 633TCP Top-Seal Adaptors. Heavy duty and corrosion resistant, the body is made of Duratuff® to help eliminate rust and oxidation for a long, maintenance-free life. The toggle lever distributes downward pressure to compress its Buna-N gasket evenly, ensuring a positive, water and vapor-tight seal. The 634TT can be locked with a padlock or wire seal.

The OPW 633TE adaptor is similar to the 633T, except it does not have internal wrenching lugs.

Materials

Cap: Die cast zinc (powder coated black)
Lever: Duratuff®
Pins: Stainless steel
Gasket: Nitrile

Ordering Specifications

Product #	in.	mm	lbs.	kg
634TT-4000	4	102	1.01	.46



634TT

OPW 634TT - Metal

The 634TT-4000 is a metal top-seal cap with the same dimensions as the 634TT-7085.

Listings and Certifications

Look for this label for authentic OPW EVR Approved products.
OPW 634TT & 634LPC are EVR Approved for E85

OPW
A DOVER COMPANY
9393 Princeton-Glendale Road ◆ Hamilton, Ohio USA 45011 Phone: (800) 422-2525 ◆ Fax: (800) 421-3297