Now Even **E-Z-R**
Visual Instructions

68EZR™
RECONNECTABLE BREAKAWAY
FAST ◆ EASY ◆ SECURE

The *Fastest, Easiest & Most Secure* Reconnectable Breakaway in the Industry

- Improved Visual Instructions
- Assurance of Connection With Clear Visual Tabs
- Audible Click to Know it is Locked and Secure
- Trusted and Proven Technology
- No Annual Maintenance
- Lowest Overall Total Cost of Ownership

PATENTED EZ-RECONNECT TECHNOLOGY INSIDE

OPW
A DOVER COMPANY

U.S. PAT. 9,528,648

See Your OPW Retailer or Equipment Provider For More Info, or Contact Us At:
(800) 422-2525 WWW.68EZR.COM

OPW 68EZR Series 3/4" and 1" Dry Reconnectable Breakaway

The OPW 68EZR Recconnectable Breakaway has been designed for retail fueling operations to deliver an increased level of security in the event of a drive off. Not only is it the fastest and easiest breakaway in the industry to reconnect, but also the one that delivers the greatest peace of mind that it is securely reconnected. Built on the 66REC breakaway technology platform, the 68EZR delivers trusted OPW quality and proven technology at the lowest cost of ownership. The 68EZR is installed on fuel dispensing hoses and will separate when subjected to a designated pull force. Upon separation, the dual valves seat automatically, stopping the flow of fuel and limiting any fuel spillage, while protecting the dispensing equipment. For proper operation on high-hanging hoses, the OPW 68EZR must always be installed with a "straightening" hose, such as the OPW 66H. For low hose applications, the OPW 68EZR should be installed downstream of the retractor cable.





Materials

3/4" 68EZR
Body: Die-cast zinc
Protective Sleeves: Impact Resistant Super-tough Nylon
Main Seals: Viton® & Fluorosilicone
Main Spring: Stainless steel
Guide and Poppets: Acetal / Delrin
Packed: 20 per Case

1" 68EZR
Body: Aluminum
Protective Sleeves: Impact Resistant Super-tough Nylon
Main Seals: Viton® & Fluorosilicone
Main Spring: Stainless steel
Guide and Poppets: Acetal / Delrin
Packed: 20 per Case

Features

- UL and ULC listed for use in gasoline, ethanol blends up to 25% (E25), diesel, and biodiesel blends up to 20% (B20). Specific listings available at **www.opwglobal.com**.
- Pull Force – the 68EZR will break away with a pull force of no more than 350 lbs.
- Unique Double-Poppet Design – features low pressure drop.
- Coupling Halves – protected by proven plastic sleeves.
- Easily Reconnected – features "Push-Twist-Click" technology; simply realign the valve, push in and then twist until you hear the audible click.
- Cold weather compatible
- Reconnection force of approximately 7 lbs.
- Line Shock – the OPW 68EZR is able to absorb the effects of normal line shock through the unique design of the disconnecting features.
- 50 psi (3.45 bar) maximum allowable operating pressure.

Ordering Specifications

Product #	Size	mm	Weight lbs.	Weight kg
68EZR-7575	3/4" (NPT)	19	1.2	0.54
68EZR-75RF*	3/4" (NPT)	19	1.2	0.54
68EZR-1010	1" (NPT)	25	1.2	0.54
68EZR-10RF**	1" (NPT)	25	1.2	0.54

*68EZR-75RF is UL and ULC listed for use in gasoline, ethanol blends up to 25% (E25), diesel, and biodiesel blends up to 20% (B20).

**68EZR-10RF is UL and ULC listed for use in diesel, and biodiesel blends up to 20% (B20).

Replacement Parts

Part #	Description
211143	3/4" Main Seal
8509	1" Main Seal

68EZR Series Instruction Sheet Order Number: **208080**





Listings and Certifications

U.S. PAT. 9,528,648

NOTE: All information subject to engineering and/or other changes. All trade names are copyrighted. Patents Pending. ©2017 OPW Fuel Management Systems. ©2017 Delaware Capital Formation, Inc. All Rights Reserved. DOVER and the DOVER logo are registered trademarks of Delaware Capital Formation, Inc., a wholly-owned subsidiary of Dover Corporation.